

## Codification of Spare Sleeves for Air operated Pinch Valves

Example Code-No.:

<b>M</b>	<b>025.</b>	<b>02X</b>	<b>K</b>		<b>FFLM</b>	<b>040.</b>	<b>03</b>
1	2	3	4		1	2	3

**1. Type:**

**M** - Sleeves

**FFLM** - Flange sleeves for VF series, DN40-100

**FLM** - Flange sleeves for VF series, DN125-200,  
as well as for old valves models type V

**2. Diameter:**

in mm

**3. Sleeve quality:**

<p><b>01X</b> = CR (neoprene)  <b>02X</b> = NR (natural rubber) food quality  <b>02LS</b> = NR food black  <b>03X</b> = NR anti-abrasive  <b>03LF</b> = NR conductive  <b>03H</b> = NR high temp.  <b>04HTEC</b> = EPDM / EPDM food black  <b>04HTECLF</b> = EPDM conductive/                            EPDM food black conductive</p>	<p><b>04LW</b> = EPDM foodpale  <b>05</b> = FPM / FKM (viton)  <b>06</b> = Silicone  <b>07X</b> = NBR (nitrile)  <b>07LS</b> = NBR foodblack  <b>07LW</b> = NBR foodpale  <b>07LF</b> = NBR conductive  <b>08X</b> = CSM (hypalon)  <b>09X</b> = IIR (butyle)</p>
---	---

**Flange sleeves (FLM/FFLM) do not include an „X“, (e.g. 01, 03)**

Variations with appendix LF (e.g. 03LF) are standing for conductive sleeves (< 10<sup>6</sup> Ohm).  
 Variations with appendix SF (e.g. 03SF) are standing for silicone-free sleeves.  
 Combinations available (e.g. ....03SFLF).

**4. Sleeves for air operated pinch valves of VMC / VMP series in nominal sizes DN10-25 are additionally marked with a K (=short length) → e.g. M020.04K**

Technical details subject to change without notice.



**Basecamp Process Components, LLC**

7685-A Corporate Blvd., Plain City, Ohio 43064, USA

T: +1 614-873-8995 • E-mail: [info@akopinvalves.com](mailto:info@akopinvalves.com) • Web: [www.akopinvalves.com](http://www.akopinvalves.com)